


TEL1X+J



x 2



x 1 (60x25x1395)



x 1 (60x25x1395)



x 4 (30x1x480)









x 4 (TCEI M8x20)




x 2 (55x20x295)




x 4 (TCEI M8x75)










1





2




3



5





20 N/m






6



7



8



COD. JR_TEL+




● = PUNTI DI FISSAGGIO CONSIGLIATI
 PER CONDIZIONI DI CARICHI NORMALI
 - NEVE fino a 1,2 KN/mq sul pannello
 - VENTO fino a velocità di 25m/s
 per carichi superiori utilizzare i cavi antivento (opzionali)
 per l'ancoraggio

Il carico consentito per il tetto e i punti di fissaggio
 devono essere controllati sul posto
 da un esperto di statica
 considerando le norme vigenti in loco.


● = SUGGESTED ANCHORING POINTS
 FOR STANDARD LOAD CONDITIONS
 - SNOW up to 1,2 kN/m² on the collector
 - WIND speed up to 25 m/s
 If wind speed is likely to overcome this limit,
 use the optional steel cables

Maximum roof load and anchoring points
 must be verified on site,
 by an engineer according to local regulations






cavi e morsetti in acciaio (opzionali) - optional steel cables






PUNTI DI FISSAGGIO CONSIGLIATI
 SUGGESTED ANCHORING POINTS




2



β	mm		N° Ø		mm
30°	X = 60	Y = 60	A = 3	B = 3	1030
35°	X = 135	Y = 135	A = 6	B = 6	1075
40°	X = 360	Y = 335	A = 15	B = 14	1200
45°	X = 510	Y = 485	A = 21	B = 20	1310
50°	X = 660	Y = 610	A = 27	B = 25	1420



3



4

